



# CHAIN CONVEYORS

1247 FLORENCE RD., FLORENCE, ON N0P 1R0 P: 1.888.239.9713 F: 519.695.2529  
sales@lambtonconveyor.com <http://www.lambtonconveyor.com>

Lambton is a trademark of Lambton Conveyor Limited.



LDB060201



# DRAG CONVEYORS

Chain sprockets for both the head and the tail are flame cut or cast from high grade steel to ensure reliability in material movement.





### Head Features:

- Computer aided modular bolt together design
- CNC manufactured
- 10-8-5 gauge standard galvanized construction
- Heavy duty pillow block bearings
- Heavy duty drive sprocket
- Removable inspection cover
- Dust seals



The steel chain is 81x and 81xH 24,000 and 44,000 lb. average ultimate strength. Welded channel attachments add rigid support for paddles. In larger capacity or long conveyors dual chains are used. Paddles are 1/2" thick UHMW CNC manufactured for accuracy. UHMW prevents metal to metal contact reducing HP requirements and increasing conveyor life.



### Trough features:

- Computer aided modular bolt together design
- CNC manufactured
- 10 gauge galvanized sides
- 10-8-5 gauge galvanized bottoms available
- UHMW return rollers
- Pre-assembled trunk sections
- Optional abrasion resistant steel liners for bottom and sides



Lambton Drag Hoppers come standard with adjustable flow gates that control the feeding capacity of the conveyor. Standard hopper lengths are 4, 8 and 12 feet in length.

\* Custom Lengths Available \*



### Tail Features:

- Computer aided modular bolt together design
- CNC Manufactured
- 10-8-5 gauge standard galvanized construction
- Heavy duty pillow block bearings
- Heavy duty sprocket
- Acme screw slack adjusters
- Removable inspection covers
- Dust seals

### Manway and Conveyor Catwalks:

- Manway and Conveyor Catwalks are designed to fit all conveyors.
- 24" standard walkway width
- Support towers are produced with same precision and rigidity as the Manway Catwalks that they support.
- X-Brace trussing is an available option for all Manway Catwalks, as is a Truss and Guy wire kit. (not shown)



The head and boot sections of the Lambton drag conveyor comes complete with long lasting roller bearings, with optional auto grease. Auto grease ensures your drag operates with the proper amount of lubrication at all times.



1247 FLORENCE RD., FLORENCE, ON N0P 1R0 P: 1.888.239.9713 F: 519.695.2529

sales@lambtonconveyor.com <http://www.lambtonconveyor.com>

